

## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	90	91	93
Total Lumens, 4' rail length (1219mm)	2662	2746	2802	2858
Lumens per foot (305mm)	666	687	701	715
Lumens per foot UP (305mm)	403	416	424	433
Lumens per foot DOWN (305mm)	263	271	276	282
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	104	108	110	112
Total Lumens, 4' rail length (1219mm)	5325	5493	5605	5717
Lumens per foot (305mm)	1331	1373	1401	1429
Lumens per foot UP (305mm)	806	831	848	865
Lumens per foot DOWN (305mm)	525	542	553	564
Input Power (W), 4' rail length (1219mm)	51.2	51.2	51.2	51.2
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	102
Total Lumens, 4' rail length (1219mm)	10117	10436	10649	10862
Lumens per foot (305mm)	2529	2609	2662	2716
Lumens per foot UP (305mm)	1531	1580	1612	1562
Lumens per foot DOWN (305mm)	998	1029	1050	1018
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	75	77	79	82
Total Lumens, 4' rail length (1219mm)	2295	2368	2416	2464
Lumens per foot (305mm)	574	592	604	616
Lumens per foot UP (305mm)	347	358	366	373
Lumens per foot DOWN (305mm)	226	234	238	243
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	90	93	95	99
Total Lumens, 4' rail length (1219mm)	4590	4735	4832	4928
Lumens per foot (305mm)	1148	1184	1208	1232
Lumens per foot UP (305mm)	695	717	731	746
Lumens per foot DOWN (305mm)	453	467	477	486
Input Power (W), 4' rail length (1219mm)	51.2	51.2	51.2	51.2
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	82	84	86	89
Total Lumens, 4' rail length (1219mm)	8721	8997	9180	9364
Lumens per foot (305mm)	2180	2249	2295	2341
Lumens per foot UP (305mm)	1320	1362	1390	1347
Lumens per foot DOWN (305mm)	860	887	905	877
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).