

**IES Report**

**ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 80 CRI | LO**



---

**707-Z3-4-48-XX-XX-X-0-Z-LO-35-U2-X-XX-X**

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	118	122	124	127
Total Lumens, 4' rail length (1219mm)	1813	1871	1909	1947
Lumens per foot (305mm)	453	468	477	487
Input Power (W), 4' rail length (1219mm)	15.4	15.4	15.4	15.4
Watts per foot (305mm)	3.9	3.9	3.9	3.9
CRI	85	85	85	85

Due to the large number of options in Vode’s product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 80 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-35-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	139	143	146	149
Total Lumens, 4' rail length (1219mm)	3627	3741	3817	3894
Lumens per foot (305mm)	907	935	954	973
Input Power (W), 4' rail length (1219mm)	26.2	26.2	26.2	26.2
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**

**ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 80 CRI | HO**



---

**707-Z3-4-48-XX-XX-X-0-Z-HO-35-U2-X-XX-X**

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	129	133	136	139
Total Lumens, 4' rail length (1219mm)	6890	7108	7253	7398
Lumens per foot (305mm)	1723	1777	1813	1850
Input Power (W), 4' rail length (1219mm)	53.6	53.6	53.6	53.6
Watts per foot (305mm)	13.4	13.4	13.4	13.4
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**

**ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 90 CRI | LO**



---

**707-Z3-4-48-XX-XX-X-0-Z-LO-359-U2-X-XX-X**

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	102	105	107	109
Total Lumens, 4' rail length (1219mm)	1563	1613	1645	1678
Lumens per foot (305mm)	391	403	411	420
Input Power (W), 4' rail length (1219mm)	15.4	15.4	15.4	15.4
Watts per foot (305mm)	3.9	3.9	3.9	3.9
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 90 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-359-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	120	124	126	129
Total Lumens, 4' rail length (1219mm)	3126	3225	3291	3357
Lumens per foot (305mm)	782	806	823	839
Input Power (W), 4' rail length (1219mm)	26.2	26.2	26.2	26.2
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 90 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-359-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	111	115	117	119
Total Lumens, 4' rail length (1219mm)	5940	6128	6253	6378
Lumens per foot (305mm)	1485	1532	1563	1594
Input Power (W), 4' rail length (1219mm)	53.6	53.6	53.6	53.6
Watts per foot (305mm)	13.4	13.4	13.4	13.4
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).