

## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 80 CRI | LO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	108	110	113	113
Total Lumens, 4' rail length (1219mm)	2962	3036	3098	3098
Lumens per foot (305mm)	741	759	775	775
Lumens per foot UP (305mm)	365	377	385	385
Lumens per foot DOWN (305mm)	370	382	390	390
Input Power (W), 4' rail length (1219mm)	27.6	27.6	27.6	27.6
Watts per foot (305mm)	7.0	7.0	7.0	7.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 80 CRI | SO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	124	127	130	130
Total Lumens, 4' rail length (1219mm)	5887	6073	6197	6197
Lumens per foot (305mm)	1472	1518	1549	1549
Lumens per foot UP (305mm)	731	754	769	769
Lumens per foot DOWN (305mm)	741	764	780	780
Input Power (W), 4' rail length (1219mm)	47.8	47.8	47.8	47.8
Watts per foot (305mm)	12.0	12.0	12.0	12.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 80 CRI | HO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	114	118	120	120
Total Lumens, 4' rail length (1219mm)	11185	11538	11774	11774
Lumens per foot (305mm)	2796	2885	2943	2943
Lumens per foot UP (305mm)	1389	1432	1462	1462
Lumens per foot DOWN (305mm)	1408	1452	1482	1482
Input Power (W), 4' rail length (1219mm)	98.1	98.1	98.1	98.1
Watts per foot (305mm)	24.6	24.6	24.6	24.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 90 CRI | LO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	95	97	98
Total Lumens, 4' rail length (1219mm)	2537	2618	2671	2698
Lumens per foot (305mm)	634	654	668	674
Lumens per foot UP (305mm)	315	325	332	335
Lumens per foot DOWN (305mm)	319	329	336	340
Input Power (W), 4' rail length (1219mm)	27.6	27.6	27.6	27.6
Watts per foot (305mm)	7.0	7.0	7.0	7.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 90 CRI | SO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	107	110	112	113
Total Lumens, 4' rail length (1219mm)	5075	5235	5342	5395
Lumens per foot (305mm)	1269	1309	1336	1349
Lumens per foot UP (305mm)	630	650	663	670
Lumens per foot DOWN (305mm)	639	659	672	679
Input Power (W), 4' rail length (1219mm)	47.8	47.8	47.8	47.8
Watts per foot (305mm)	12.0	12.0	12.0	12.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 90 CRI | HO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	99	102	104	105
Total Lumens, 4' rail length (1219mm)	9642	9947	10150	10251
Lumens per foot (305mm)	2411	2487	2537	2563
Lumens per foot UP (305mm)	1197	1235	1260	1273
Lumens per foot DOWN (305mm)	1214	1252	1277	1290
Input Power (W), 4' rail length (1219mm)	98.1	98.1	98.1	98.1
Watts per foot (305mm)	24.6	24.6	24.6	24.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).