

IES Report



WingRail® | 107 | White Baffle with EdgeSoft™ | 80 CRI | LO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	94	96	96
Total Lumens, 4' rail length (1219mm)	1258	1298	1325	1325
Lumens per foot (305mm)	315	325	331	331
Input Power (W), 4' rail length (1219mm)	13.8	13.8	13.8	13.8
Watts per foot (305mm)	3.5	3.5	3.5	3.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



WingRail® | 107 | White Baffle with EdgeSoft™ | 80 CRI | SO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	106	109	111	111
Total Lumens, 4' rail length (1219mm)	2517	2596	2649	2649
Lumens per foot (305mm)	629	649	662	662
Input Power (W), 4' rail length (1219mm)	23.9	23.9	23.9	23.9
Watts per foot (305mm)	6.0	6.0	6.0	6.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



WingRail® | 107 | White Baffle with EdgeSoft™ | 80 CRI | HO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	98	101	103	103
Total Lumens, 4' rail length (1219mm)	4782	4933	5034	5034
Lumens per foot (305mm)	1195	1233	1258	1258
Input Power (W), 4' rail length (1219mm)	49.1	49.1	49.1	49.1
Watts per foot (305mm)	12.3	12.3	12.3	12.3
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



WingRail® | 107 | White Baffle with EdgeSoft™ | 90 CRI | LO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	79	82	83	84
Total Lumens, 4' rail length (1219mm)	1085	1119	1142	1153
Lumens per foot (305mm)	271	280	285	288
Input Power (W), 4' rail length (1219mm)	13.8	13.8	13.8	13.8
Watts per foot (305mm)	3.5	3.5	3.5	3.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



WingRail® | 107 | White Baffle with EdgeSoft™ | 90 CRI | SO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	94	96	97
Total Lumens, 4' rail length (1219mm)	2170	2238	2284	2307
Lumens per foot (305mm)	542	560	571	577
Input Power (W), 4' rail length (1219mm)	24.0	24.0	24.0	24.0
Watts per foot (305mm)	6.0	6.0	6.0	6.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

WingRail® | 107 | White Baffle with EdgeSoft™ | 90 CRI | HO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	84	87	89	90
Total Lumens, 4' rail length (1219mm)	4122	4252	4339	4383
Lumens per foot (305mm)	1031	1063	1085	1096
Input Power (W), 4' rail length (1219mm)	49.1	49.1	49.1	49.1
Watts per foot (305mm)	12.3	12.3	12.3	12.3
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).