

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	94	97	99	99
Total Lumens, 4' rail length (1219mm)	2773	2860	2919	2919
Lumens per foot (305mm)	693	715	730	730
Lumens per foot UP (305mm)	474	489	499	499
Lumens per foot DOWN (305mm)	219	226	231	231
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	107	110	112	112
Total Lumens, 4' rail length (1219mm)	5545	5720	5837	5837
Lumens per foot (305mm)	1386	1430	1459	1459
Lumens per foot UP (305mm)	948	978	998	998
Lumens per foot DOWN (305mm)	438	452	461	461
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	98	101	104	104
Total Lumens, 4' rail length (1219mm)	10536	10869	11090	11090
Lumens per foot (305mm)	2634	2717	2773	2773
Lumens per foot UP (305mm)	1801	1858	1896	1896
Lumens per foot DOWN (305mm)	833	859	877	877
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	81	83	85	88
Total Lumens, 4' rail length (1219mm)	2390	2466	2516	2541
Lumens per foot (305mm)	598	616	629	635
Lumens per foot UP (305mm)	409	421	430	434
Lumens per foot DOWN (305mm)	189	195	199	201
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	93	96	98	102
Total Lumens, 4' rail length (1219mm)	4780	4931	5032	5082
Lumens per foot (305mm)	1195	1233	1258	1271
Lumens per foot UP (305mm)	817	843	860	869
Lumens per foot DOWN (305mm)	378	390	398	402
Input Power (W), 4' rail length (1219mm)	51.7	51.7	51.7	51.7
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	85	88	89	93
Total Lumens, 4' rail length (1219mm)	9083	9370	9561	9656
Lumens per foot (305mm)	2271	2342	2390	2414
Lumens per foot UP (305mm)	1553	1602	1634	1651
Lumens per foot DOWN (305mm)	718	741	756	763
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.