

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	107	110	112	112
Total Lumens, 4' rail length (1219mm)	3167	3267	3334	3334
Lumens per foot (305mm)	792	817	833	833
Lumens per foot UP (305mm)	497	513	524	524
Lumens per foot DOWN (305mm)	294	304	310	310
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	122	126	128	128
Total Lumens, 4' rail length (1219mm)	6334	6534	6667	6667
Lumens per foot (305mm)	1583	1633	1667	1667
Lumens per foot UP (305mm)	995	1026	1047	1047
Lumens per foot DOWN (305mm)	589	607	620	620
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	112	116	118	118
Total Lumens, 4' rail length (1219mm)	12034	12414	12667	12667
Lumens per foot (305mm)	3009	3104	3167	3167
Lumens per foot UP (305mm)	1890	1950	1990	1990
Lumens per foot DOWN (305mm)	1118	1154	1177	1177
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	95	97	101
Total Lumens, 4' rail length (1219mm)	2730	2816	2874	2902
Lumens per foot (305mm)	683	704	718	726
Lumens per foot UP (305mm)	429	442	451	456
Lumens per foot DOWN (305mm)	254	262	267	270
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	106	109	111	115
Total Lumens, 4' rail length (1219mm)	5460	5633	5747	5805
Lumens per foot (305mm)	1365	1408	1437	1451
Lumens per foot UP (305mm)	858	885	903	912
Lumens per foot DOWN (305mm)	507	524	534	540
Input Power (W), 4' rail length (1219mm)	51.8	51.8	51.8	51.8
Watts per foot (305mm)	13	13	13	13
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	97	100	102	106
Total Lumens, 4' rail length (1219mm)	10374	10702	10920	11029
Lumens per foot (305mm)	2594	2675	2730	2757
Lumens per foot UP (305mm)	1629	1681	1715	1732
Lumens per foot DOWN (305mm)	964	995	1015	1025
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.