



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2D2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	120	124	126	126
Total Lumens, 4' rail length (1219mm)	3552	3664	3739	3739
Lumens per foot (305mm)	888	916	935	935
Lumens per foot UP (305mm)	499	515	525	525
Lumens per foot DOWN (305mm)	389	401	409	409
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2D2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	136	141	144	144
Total Lumens, 4' rail length (1219mm)	7104	7329	7478	7478
Lumens per foot (305mm)	1776	1832	1870	1870
Lumens per foot UP (305mm)	998	1030	1051	1051
Lumens per foot DOWN (305mm)	778	803	819	819
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](https://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2D2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	126	130	132	132
Total Lumens, 4' rail length (1219mm)	13498	13925	14209	14209
Lumens per foot (305mm)	3375	3481	3552	3552
Lumens per foot UP (305mm)	1896	1956	1996	1996
Lumens per foot DOWN (305mm)	1478	1525	1556	1556
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2D2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	103	107	109	110
Total Lumens, 4' rail length (1219mm)	3062	3159	3223	3256
Lumens per foot (305mm)	766	790	806	814
Lumens per foot UP (305mm)	430	444	453	457
Lumens per foot DOWN (305mm)	335	346	353	357
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI*	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2D2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	119	123	125	126
Total Lumens, 4' rail length (1219mm)	6124	6318	6447	6511
Lumens per foot (305mm)	1531	1579	1612	1628
Lumens per foot UP (305mm)	860	888	906	915
Lumens per foot DOWN (305mm)	671	692	706	713
Input Power (W), 4' rail length (1219mm)	51.7	51.7	51.7	51.7
Watts per foot (305mm)	13.0	13.0	13.0	13.0
CRI*	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2D2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	109	112	114	115
Total Lumens, 4' rail length (1219mm)	11636	12004	12249	12371
Lumens per foot (305mm)	2909	3001	3062	3093
Lumens per foot UP (305mm)	1635	1686	1721	1738
Lumens per foot DOWN (305mm)	1274	1315	1341	1355
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI*	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).