



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	111	115	117	117
Total Lumens, 4' rail length (1219mm)	3303	3407	3477	3477
Lumens per foot (305mm)	476	491	501	501
Lumens per foot UP (305mm)	350	361	368	368
Lumens per foot DOWN (305mm)	826	852	869	869
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	127	131	134	134
Total Lumens, 4' rail length (1219mm)	6606	6814	6953	6953
Lumens per foot (305mm)	952	982	1002	1002
Lumens per foot UP (305mm)	699	721	736	736
Lumens per foot DOWN (305mm)	1651	1704	1738	1738
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



**IES Report**



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	117	121	123	123
Total Lumens, 4' rail length (1219mm)	12551	12947	13211	13211
Lumens per foot (305mm)	1809	1866	1904	1904
Lumens per foot UP (305mm)	1329	1371	1399	1399
Lumens per foot DOWN (305mm)	3138	3237	3303	3303
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**

**ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 90 CRI | LO**



---

**707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2D2-0-BL-X**

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	96	99	101	102
Total Lumens, 4' rail length (1219mm)	2847	2937	2997	3027
Lumens per foot (305mm)	410	423	432	436
Lumens per foot UP (305mm)	301	311	317	320
Lumens per foot DOWN (305mm)	712	734	749	757
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	113	115	116
Total Lumens, 4' rail length (1219mm)	5695	5874	5994	6054
Lumens per foot (305mm)	821	847	864	873
Lumens per foot UP (305mm)	603	622	635	641
Lumens per foot DOWN (305mm)	1424	1469	1499	1514
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](https://vode.com).



## IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | Soft Diffuse, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	101	104	106	107
Total Lumens, 4' rail length (1219mm)	10820	11161	11389	11503
Lumens per foot (305mm)	1559	1609	1641	1658
Lumens per foot UP (305mm)	1146	1182	1206	1218
Lumens per foot DOWN (305mm)	2705	2790	2847	2876
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).