

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	105	108	110	110
Total Lumens, 4' rail length (1219mm)	3109	3207	3273	3273
Lumens per foot (305mm)	777	802	818	818
Lumens per foot UP (305mm)	486	502	512	512
Lumens per foot DOWN (305mm)	291	300	306	306
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	120	123	126	126
Total Lumens, 4' rail length (1219mm)	6218	6414	6545	6545
Lumens per foot (305mm)	1555	1604	1636	1636
Lumens per foot UP (305mm)	973	1003	1024	1024
Lumens per foot DOWN (305mm)	582	600	612	612
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	114	116	116
Total Lumens, 4' rail length (1219mm)	11814	12187	12436	12436
Lumens per foot (305mm)	2954	3047	3109	3109
Lumens per foot UP (305mm)	1848	1907	1946	1946
Lumens per foot DOWN (305mm)	1105	1140	1164	1164
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	93	95	99
Total Lumens, 4' rail length (1219mm)	2680	2765	2821	2849
Lumens per foot (305mm)	670	691	705	712
Lumens per foot UP (305mm)	419	433	441	446
Lumens per foot DOWN (305mm)	251	259	264	267
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	104	107	109	113
Total Lumens, 4' rail length (1219mm)	5360	5530	5643	5699
Lumens per foot (305mm)	1340	1382	1411	1425
Lumens per foot UP (305mm)	839	865	883	892
Lumens per foot DOWN (305mm)	502	517	528	533
Input Power (W), 4' rail length (1219mm)	51.8	51.8	51.8	51.8
Watts per foot (305mm)	13	13	13	13
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	104
Total Lumens, 4' rail length (1219mm)	10185	10506	10721	10828
Lumens per foot (305mm)	2546	2627	2680	2707
Lumens per foot UP (305mm)	1593	1644	1677	1694
Lumens per foot DOWN (305mm)	953	983	1003	1013
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.