

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	113	116	116
Total Lumens, 4' rail length (1219mm)	3260	3363	3432	3432
Lumens per foot (305mm)	815	841	858	858
Lumens per foot UP (305mm)	465	479	489	489
Lumens per foot DOWN (305mm)	350	361	369	369
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	125	129	132	132
Total Lumens, 4' rail length (1219mm)	6520	6726	6863	6863
Lumens per foot (305mm)	1630	1682	1716	1716
Lumens per foot UP (305mm)	929	959	978	978
Lumens per foot DOWN (305mm)	701	723	737	737
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	116	119	122	122
Total Lumens, 4' rail length (1219mm)	12388	12780	13040	13040
Lumens per foot (305mm)	3097	3195	3260	3260
Lumens per foot UP (305mm)	1766	1822	1859	1859
Lumens per foot DOWN (305mm)	1331	1373	1401	1401
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	104
Total Lumens, 4' rail length (1219mm)	2810	2899	2958	2988
Lumens per foot (305mm)	703	725	740	747
Lumens per foot UP (305mm)	401	413	422	426
Lumens per foot DOWN (305mm)	302	312	318	321
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	109	113	115	120
Total Lumens, 4' rail length (1219mm)	5621	5798	5917	5976
Lumens per foot (305mm)	1405	1450	1479	1494
Lumens per foot UP (305mm)	801	827	843	852
Lumens per foot DOWN (305mm)	604	623	636	642
Input Power (W), 4' rail length (1219mm)	51.7	51.7	51.7	51.7
Watts per foot (305mm)	13	13	13	13
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	100	103	105	109
Total Lumens, 4' rail length (1219mm)	10680	11017	11242	11354
Lumens per foot (305mm)	2670	2754	2810	2839
Lumens per foot UP (305mm)	1522	1570	1603	1619
Lumens per foot DOWN (305mm)	1148	1184	1208	1220
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.