

## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	101	104	106	106
Total Lumens, 4' rail length (1219mm)	2990	3085	3148	3148
Lumens per foot (305mm)	748	771	787	787
Lumens per foot UP (305mm)	445	459	468	468
Lumens per foot DOWN (305mm)	303	313	319	319
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	115	119	121	121
Total Lumens, 4' rail length (1219mm)	5980	6169	6295	6295
Lumens per foot (305mm)	1495	1542	1574	1574
Lumens per foot UP (305mm)	889	917	936	936
Lumens per foot DOWN (305mm)	606	625	638	638
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	106	109	112	112
Total Lumens, 4' rail length (1219mm)	11363	11722	11961	11961
Lumens per foot (305mm)	2841	2930	2990	2990
Lumens per foot UP (305mm)	1690	1743	1778	1778
Lumens per foot DOWN (305mm)	1151	1188	1212	1212
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



# ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	90	92	96
Total Lumens, 4' rail length (1219mm)	2578	2659	2713	2741
Lumens per foot (305mm)	644	665	678	685
Lumens per foot UP (305mm)	383	395	403	407
Lumens per foot DOWN (305mm)	261	269	275	278
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	99	102	104	108
Total Lumens, 4' rail length (1219mm)	5156	5318	5427	5481
Lumens per foot (305mm)	1289	1330	1357	1370
Lumens per foot UP (305mm)	767	791	807	815
Lumens per foot DOWN (305mm)	522	539	550	555
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | 80° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	94	96	100
Total Lumens, 4' rail length (1219mm)	9796	10105	10311	10414
Lumens per foot (305mm)	2449	2526	2578	2604
Lumens per foot UP (305mm)	1456	1502	1533	1548
Lumens per foot DOWN (305mm)	992	1024	1045	1055
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).