

IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 80 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-35-A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	86	89	91	91
Total Lumens, 4' rail length (1219mm)	1280	1321	1347	1347
Lumens per foot (305mm)	320	330	337	337
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 80 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-35-A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	99	102	104	104
Total Lumens, 4' rail length (1219mm)	2560	2641	2695	2695
Lumens per foot (305mm)	640	660	674	674
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 80 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-35-A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	94	96	96
Total Lumens, 4' rail length (1219mm)	4864	5018	5120	5120
Lumens per foot (305mm)	1216	1254	1280	1280
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 90 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-359-A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	75	77	78	81
Total Lumens, 4' rail length (1219mm)	1104	1138	1162	1173
Lumens per foot (305mm)	276	285	290	293
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 90 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-359-A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	85	88	89	93
Total Lumens, 4' rail length (1219mm)	2207	2277	2323	2346
Lumens per foot (305mm)	552	569	581	587
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipThree® | 707 | 85° Asymmetric , downlight only | 90 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-359-A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	78	81	83	86
Total Lumens, 4' rail length (1219mm)	4193	4326	4414	4458
Lumens per foot (305mm)	1048	1081	1104	1115
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).