

IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 80 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-35-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	135	140	143	143
Total Lumens, 4' rail length (1219mm)	2009	2073	2115	2115
Lumens per foot (305mm)	502	518	529	529
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 80 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-35-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	154	159	162	162
Total Lumens, 4' rail length (1219mm)	4019	4146	4230	4230
Lumens per foot (305mm)	1005	1036	1058	1058
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 80 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-35-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	142	147	150	150
Total Lumens, 4' rail length (1219mm)	7635	7877	8037	8037
Lumens per foot (305mm)	1909	1969	2009	2009
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 90 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-359-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	117	120	123	124
Total Lumens, 4' rail length (1219mm)	1732	1787	1823	1842
Lumens per foot (305mm)	433	447	456	460
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 90 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-359-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	133	137	140	141
Total Lumens, 4' rail length (1219mm)	3464	3574	3647	3683
Lumens per foot (305mm)	866	893	912	921
Input Power (W), 4' rail length (1219mm)	26.2	26.2	26.2	26.2
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipThree® | 707 | Symmetric with EdgeGlow™, uplight only | 90 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-359-U2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	123	127	129	131
Total Lumens, 4' rail length (1219mm)	6582	6790	6929	6998
Lumens per foot (305mm)	1646	1698	1732	1750
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).