

IES Report



ZipThree® | 707 | Symmetric, uplight only | 80 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-35-U1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	133	137	140	140
Total Lumens, 4' rail length (1219mm)	1968	2030	2072	2072
Lumens per foot (305mm)	492	508	518	518
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric, uplight only | 80 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-35-U1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	151	156	159	159
Total Lumens, 4' rail length (1219mm)	3936	4061	4144	4144
Lumens per foot (305mm)	984	1015	1036	1036
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric, uplight only | 80 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-35-U1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	139	144	147	147
Total Lumens, 4' rail length (1219mm)	7479	7715	7873	7873
Lumens per foot (305mm)	1870	1929	1968	1968
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric, uplight only | 90 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-359-U1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	115	119	121	122
Total Lumens, 4' rail length (1219mm)	1705	1759	1795	1813
Lumens per foot (305mm)	426	440	449	453
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | Symmetric, uplight only | 90 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-359-U1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	131	135	137	139
Total Lumens, 4' rail length (1219mm)	3393	3501	3572	3608
Lumens per foot (305mm)	848	875	893	902
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipThree® | 707 | Symmetric, uplight only | 90 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-359-U1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	122	126	128	130
Total Lumens, 4' rail length (1219mm)	6537	6743	6881	6950
Lumens per foot (305mm)	1634	1686	1720	1737
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).