

IES Report

ZipTwo® | 707 | 60° Symmetric | 80 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-35-S2-X-BL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	61	63	64	64
Total Lumens, 4' rail length (1219mm)	1584	1634	1667	1667
Lumens per foot (305mm)	396	408	417	417
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES INDOOR REPORT

PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2_BL.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] L121911528 (SOURCE REPORT FOR REFERENCE)

[TESTLAB] REPORT BASED ON DATA FROM NVLAP ACCREDITED LAB

[ISSUE DATE] 12/23/2019

[MANUFAC] Vode Lighting

[LUMCAT] 707-Z2-48-Z-SO-35-S2-BL

[LUMINAIRE] ZipTwo LED, 48", 3500K, 80 CRI, zipper board, 60° black symmetric lens,

[MORE] standard output, black anodized finish

[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1667
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	64
Total Luminaire Watts	26.11
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.84
Spacing Criterion (90-270)	1.08
Spacing Criterion (Diagonal)	0.96
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.02 ft
Luminous Width (90-270)	3.98 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	31028	53080	79786
55	14481	26229	41257
65	8158	14091	21878
75	4844	8477	13321
85	3596	5394	7192

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2_BL.IES

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
0.0	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40
1.0	1381.56	1380.40	1380.40	1381.56	1380.40	1380.40	1380.40	1380.40	1381.56	1381.56
3.0	1374.60	1374.60	1374.60	1374.60	1375.76	1375.76	1375.76	1375.76	1376.92	1376.92
5.0	1360.68	1360.68	1360.68	1360.68	1361.84	1363.00	1364.16	1364.16	1365.32	1366.48
7.0	1336.32	1336.32	1337.48	1338.64	1339.80	1342.12	1343.28	1345.60	1349.08	1351.40
9.0	1305.00	1303.84	1306.16	1307.32	1310.80	1313.12	1316.60	1320.08	1325.88	1329.36
11.0	1262.08	1262.08	1264.40	1266.72	1270.20	1276.00	1281.80	1287.60	1293.40	1300.36
13.0	1211.04	1212.20	1214.52	1218.00	1223.80	1230.76	1238.88	1248.16	1257.44	1265.56
15.0	1151.88	1153.04	1157.68	1162.32	1170.44	1178.56	1189.00	1200.60	1213.36	1224.96
17.0	1085.76	1088.08	1091.56	1098.52	1107.80	1119.40	1132.16	1147.24	1163.48	1178.56
19.5	994.12	995.28	1001.08	1009.20	1021.96	1037.04	1053.28	1071.84	1091.56	1111.28
22.5	873.48	875.80	882.76	893.20	908.28	925.68	947.72	970.92	995.28	1020.80
25.5	747.04	749.36	757.48	769.08	786.48	807.36	831.72	858.40	888.56	918.72
29.0	603.20	605.52	614.80	627.56	646.12	669.32	694.84	725.00	757.48	791.12
33.0	453.56	455.88	464.00	476.76	494.16	517.36	544.04	575.36	609.00	643.80
37.5	313.20	315.52	322.48	332.92	349.16	368.88	393.24	421.08	452.40	486.04
42.5	199.52	200.68	206.48	214.60	226.20	242.44	261.00	283.04	307.40	334.08
47.5	125.28	126.44	129.92	135.72	143.84	154.28	168.20	184.44	201.84	221.56
55.0	61.48	62.64	63.80	67.28	71.92	76.56	83.52	92.80	102.08	111.36
65.0	25.52	25.52	25.52	26.68	29.00	31.32	33.64	37.12	40.60	44.08
75.0	9.28	9.28	10.44	10.44	11.60	11.60	12.76	13.92	15.08	16.24
85.0	2.32	2.32	2.32	2.32	2.32	3.48	3.48	3.48	3.48	3.48
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles **Horizontal Angles**

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
0.0	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40	1380.40
1.0	1380.40	1380.40	1381.56	1381.56	1381.56	1381.56	1381.56	1381.56	1380.40
3.0	1376.92	1378.08	1378.08	1378.08	1378.08	1378.08	1378.08	1379.24	1379.24
5.0	1367.64	1368.80	1371.12	1371.12	1372.28	1372.28	1373.44	1373.44	1373.44
7.0	1353.72	1356.04	1358.36	1360.68	1361.84	1364.16	1365.32	1365.32	1365.32
9.0	1334.00	1338.64	1340.96	1345.60	1347.92	1350.24	1352.56	1352.56	1352.56
11.0	1307.32	1313.12	1318.92	1324.72	1329.36	1332.84	1335.16	1336.32	1336.32
13.0	1274.84	1284.12	1292.24	1299.20	1306.16	1310.80	1314.28	1316.60	1317.76
15.0	1237.72	1249.32	1259.76	1270.20	1278.32	1285.28	1289.92	1293.40	1294.56
17.0	1193.64	1208.72	1222.64	1235.40	1245.84	1253.96	1260.92	1264.40	1264.40
19.5	1132.16	1151.88	1169.28	1184.36	1198.28	1208.72	1216.84	1220.32	1222.64
22.5	1047.48	1070.68	1092.72	1111.28	1127.52	1142.60	1151.88	1157.68	1160.00
25.5	948.88	976.72	1003.40	1027.76	1047.48	1062.56	1074.16	1081.12	1083.44
29.0	825.92	858.40	888.56	916.40	939.60	957.00	970.92	977.88	980.20
33.0	679.76	714.56	748.20	777.20	801.56	820.12	832.88	842.16	844.48
37.5	519.68	553.32	584.64	612.48	636.84	654.24	667.00	675.12	677.44
42.5	364.24	390.92	417.60	440.80	460.52	475.60	486.04	493.00	495.32
47.5	242.44	262.16	281.88	298.12	313.20	324.80	332.92	337.56	339.88
55.0	122.96	133.40	142.68	151.96	160.08	167.04	171.68	174.00	175.16
65.0	47.56	52.20	55.68	59.16	62.64	64.96	67.28	68.44	68.44
75.0	17.40	18.56	19.72	22.04	23.20	24.36	24.36	25.52	25.52
85.0	3.48	3.48	4.64	4.64	4.64	4.64	4.64	4.64	4.64
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2_BL.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	450.26	N.A.	27.00
0-30	855.40	N.A.	51.30
0-40	1179.96	N.A.	70.80
0-60	1546.77	N.A.	92.80
0-80	1655.06	N.A.	99.30
0-90	1667.1	N.A.	100.00
10-90	1562.18	N.A.	93.70
20-40	729.70	N.A.	43.80
20-50	986.72	N.A.	59.20
40-70	443.02	N.A.	26.60
60-80	108.29	N.A.	6.50
70-80	32.08	N.A.	1.90
80-90	12.04	N.A.	0.70
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1667.1	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	104.92
10-20	345.34
20-30	405.13
30-40	324.56
40-50	257.02
50-60	109.78
60-70	76.21
70-80	32.08
80-90	12.04
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2_BL.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	101	102	100	97	98	96	94	95	93	92	90
2	104	98	93	89	102	96	92	88	93	89	86	90	87	84	87	84	82	80
3	98	89	83	78	95	88	82	78	85	80	76	83	79	75	80	77	74	72
4	91	82	75	70	89	81	74	69	78	73	68	76	71	68	74	70	67	65
5	85	75	68	63	84	74	68	62	72	66	62	70	65	61	69	64	61	59
6	80	69	62	57	79	69	62	57	67	61	56	65	60	56	64	59	55	54
7	75	64	57	52	74	64	57	52	62	56	52	61	55	51	60	55	51	49
8	71	60	53	48	70	59	52	48	58	52	47	57	51	47	56	51	47	45
9	67	56	49	44	66	55	49	44	54	48	44	53	48	44	52	47	44	42
10	63	52	45	41	62	52	45	41	51	45	41	50	44	41	49	44	40	39

POLAR GRAPH



Maximum Candela = 1381.56 Located At Horizontal Angle = 0, Vertical Angle = 1
1 - Vertical Plane Through Horizontal Angles (0 - 180)
2 - Horizontal Cone Through Vertical Angle (1) (Through Max. Cd.)