

IES Report



ZipTwo® | 707 | Diffuse | 80 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-35-D3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	130	134	137	137
Total Lumens, 4' rail length (1219mm)	1924	1985	2026	2026
Lumens per foot (305mm)	481	496	506	506
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Diffuse | 80 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-35-D3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	148	153	157	156
Total Lumens, 4' rail length (1219mm)	3849	3970	4051	4051
Lumens per foot (305mm)	962	993	1013	1013
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Diffuse | 80 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-35-D3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	146	151	154	154
Total Lumens, 4' rail length (1219mm)	5773	5956	6077	6077
Lumens per foot (305mm)	1443	1489	1519	1519
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Diffuse | 90 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-359-D3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	112	115	118	119
Total Lumens, 4' rail length (1219mm)	1659	1711	1746	1764
Lumens per foot (305mm)	415	428	437	441
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Diffuse | 90 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-359-D3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	127	131	134	135
Total Lumens, 4' rail length (1219mm)	3318	3423	3493	3528
Lumens per foot (305mm)	829	856	873	882
Input Power (W), 4' rail length (1219mm)	26.2	26.2	26.1	26.2
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipTwo® | 707 | Diffuse | 90 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-359-D3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	126	130	133	134
Total Lumens, 4' rail length (1219mm)	4977	5134	5239	5291
Lumens per foot (305mm)	1244	1284	1310	1323
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).