

IES Report



ZipTwo® | 707 | Square 3536/30, Soft Wash | 80 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-35-A3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	89	92	94	94
Total Lumens, 4' rail length (1219mm)	1317	1358	1386	1386
Lumens per foot (305mm)	329	340	347	347
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536/30, Soft Wash | 80 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-35-A3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	101	105	107	107
Total Lumens, 4' rail length (1219mm)	2634	2717	2772	2772
Lumens per foot (305mm)	658	679	693	693
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536/30, Soft Wash | 80 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-35-A3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	100	104	106	106
Total Lumens, 4' rail length (1219mm)	3950	4075	4158	4158
Lumens per foot (305mm)	988	1019	1040	1040
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536/30, Soft Wash | 90 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-359-A3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	77	79	81	82
Total Lumens, 4' rail length (1219mm)	1135	1171	1195	1207
Lumens per foot (305mm)	284	293	299	302
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	95	95	95	95

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536/30, Soft Wash | 90 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-359-A3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	88	90	92	93
Total Lumens, 4' rail length (1219mm)	2270	2342	2390	2414
Lumens per foot (305mm)	568	585	597	603
Input Power (W), 4' rail length (1219mm)	26.0	26.0	26.0	26.0
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	95	95	95	95

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipTwo® | 707 | Square 3536/30, Soft Wash | 90 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-359-A3-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	89	91	92
Total Lumens, 4' rail length (1219mm)	3405	3513	3585	3621
Lumens per foot (305mm)	851	878	896	905
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	95	95	95	95

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).