

IES Report



ZipTwo® | 707 | Square 3536, Critical Edge | 80 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-35-S5-X-BL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	76	78	79	79
Total Lumens, 4' rail length (1219mm)	1117	1152	1176	1176
Lumens per foot (305mm)	279	288	294	294
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536, Critical Edge | 80 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-35-S5-X-BL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	86	89	91	91
Total Lumens, 4' rail length (1219mm)	2234	2305	2352	2352
Lumens per foot (305mm)	559	576	588	588
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536, Critical Edge | 80 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-35-S5-X-BL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	85	88	90	90
Total Lumens, 4' rail length (1219mm)	3352	3457	3528	3528
Lumens per foot (305mm)	838	864	882	882
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536, Critical Edge | 90 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-359-S5-X-BL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	65	67	69	69
Total Lumens, 4' rail length (1219mm)	963	994	1014	1024
Lumens per foot (305mm)	241	248	253	256
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	95	95	95	95

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square 3536, Critical Edge | 90 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-359-S5-X-BL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	74	77	78	79
Total Lumens, 4' rail length (1219mm)	1926	1987	2028	2048
Lumens per foot (305mm)	482	497	507	512
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	95	95	95	95

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipTwo® | 707 | Square 3536, Critical Edge | 90 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-359-S5-X-BL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	74	76	77	78
Total Lumens, 4' rail length (1219mm)	2889	2981	3041	3072
Lumens per foot (305mm)	722	745	760	768
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	95	95	95	95

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).